

ALUM SLIDE IN SPEC SHEET FOR COMMON SIZES

	WIDTH	HEIGHT	LENGTH	AS WEIGHED TANK ONLY SUPER 6	AS WEIGHED CRATED SUPER 6	SHIPPING WEIGHT Super 6
300 GALLON	47"	58"	73"	approx 725		
300 crated	62"	65"	100"		885	1013 + 10 battery
450 GALLON	47"	58"	93"	approx 820		
450 crated	62"	65"	100"		980	1127 + 10 battery
600 GALLON	51"	58"	113"	approx 980		
600 crated	62"	65"	124"		1180	1327 + 10 battery
600 SPECIAL	59"	66"	93"	approx 980		
600 SP crated	74"	73"	100"		1180	1327 + 10 battery
800 GALLON	59"	66"	113"	approx 1120		
800 crated	74"	73"	124"		1340	1483 + 10 battery
995 GALLON	65"	72"	113"			
995 crated	74"	79	124"			

NOTES:

MAXIMUM VACUUM 18 HG, MAXIMUM PRESSURE 7 PSIG

WEIGHTS WILL VARY FOR VACUUM ONLY UNITS TO UNITS WITH FRESH WATER FILL

HOSE HOOKS ADD 7" TO THE WIDTH BUT ARE MOUNTED ABOVE PICKUP BOX LEVEL

A 54" DIAMETER TANK WILL EASILY FIT BETWEEN THE WHEEL WELLS IN A STANDARD PICKUP BED

THE LENGTH SHOWN IS THE LENGTH OF THE 6" X 3" FRAME RAIL

IT MAY BE POSSIBLE TO BUILD A LARGER DIAMETER TANK IN ORDER TO REDUCE THE OVERALL LENGTH

PUMP PLATFORM APPROX 28" LONG

SOME OF THE LARGER PUMPS WILL HANG OVER THE PLATFORM AND ADD AN ADDITIONAL 3" TO THE OVERALL LENGTH

20" MANWAY IS 1 3/4" TALLER THAN PRIMARY SCRUBBER (DISTANCE FROM BOTTOM OF LUG BRACKET TO TOP OF COVER)

CONDE WEIGHTS; SUPER 6 - 160 LBS, SDS6 - 200 LBS, SDS12 - 275 LBS